



Product data sheet

PENDANT LUMINAIRE LIGHTUP OFFICE 87W CRI > 80 3000K NATURAL
2006.8211 - LGTUP PEN2364-1600 LED11400-830 Q48 ELOX DALI
REGENT



Pendant luminaire Lightup Office with LED, system power: 87 W, standby power 0.5 W, luminous flux of luminaire 11400 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, (70%/30%), frame in aluminium natural-colour anodised, specular louvre in synthetic material satin, 1 integral control gear, DALI, with 2 steel suspension cables are infinitely adjustable in height and can be aligned horizontally as required protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1249123 L = 2364 mm, B = 68 mm, H = 58 mm, p = 1600 mm

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	87 W	CRI	80
Total flux	11400 lm	LOR	100%
Luminous efficacy	131 lm/W	ULOR	30%
		Total power	87 W

Mounting mode

Pendant

Shape and measurements

Length: 93.07 in
Width: 2.68 in
Height: 2.28 in
Weight: 7.928 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 87 W
Appliance Class: I

Protection

IP: 20