
Product data sheet


841 MINICOMFORT LED X3 - UGR<LT/>16 4000K CRI 90 28W CLD WHITE
153538-00
DISANO



IP 20 IK 07

Housing: galvanised steel. Optics: dark light double parabolic louvers in high gloss 99.99 aluminium, anti-dazzle and anti-iridescent, very low luminance, and PDV treatment. : UGR<lt/>16, according to standard EN 12464. Coating: pre-painted in oven with polyester resin, UV-stabilised, phosphate pre-treatment. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: with film to protect the ceiling fixture and the baffle louvre. supplied without brackets: for non-surface mounting, use brackets acc. 326. On request: - DIMM wiring and built-in multisensor, subcode -0092 (1-10V). - CLD-EC wiring for centrally powered emergency lighting (subcode -0050) - CLD-D (PUSH) (subcode -0045)

Light output 1



1 x STW8QQ_841_3x_90

Nominal lamp power	28 W	LOR	100%
Lamp flux	2924 lm	Total flux	2924 lm
Luminous efficacy	104 lm/W	Total power	28 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.46 in
Width: 23.46 in
Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 28 W
Appliance Class: I

Protection

IP: 20
IK: 07
Designation labels: CE, ENEC