


# Product data sheet

HIGH BAY DALI GEN 3 155 W 4000 K 110DEG IP65  
4058075543928  
LEDVANCE



LED high-bay luminaires with DALI interface. Product features: Pre-configured DALI driver included. Luminous efficacy: up to 140 lm/W. Type of protection: IP65. Dimming range (DALI): 10...100 %. Product benefits: High compatibility thanks to DALI-2 certification. DALI 2.0 interface for dimming and sensor operations. Low flicker light thanks to special electronic control gear. High luminous efficacy. Energy savings of up to 90 % compared to conventional high bay luminaires. 5 years guarantee. Areas of application: Replacement for high bay luminaires with mercury vapor or metal halide lamps. Warehouses. Logistics halls. Industry. High ceiling (e.g. in shopping malls, airports, commercial buildings, lobbies). Equipment / Accessories: Mounting hook and brackets included. Reflectors and refractors as separate accessory available.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	155 W	CRI	80
Total flux	22000 lm	LOR	100%
Luminous efficacy	142 lm/W	Total power	155 W

## Mounting mode

Pendant, Ceiling mounted

## Shape and measurements

Length: 12.64 in  
Width: 12.64 in  
Height: 6.46 in  
Weight: 3.568 kg

## Adjustability

Fixed

## Design

Material impression: Aluminum  
Color of housing: Black

## Electric

System power: 155 W  
Appliance Class: I

## Protection

IP: 65  
IK: 08  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: -22...122°F