


Product data sheet

SRN L38 PC LE3
SIREN EMERGENCY
DEXTRA




Siren - 1200mm, IP65, IK07 Surface mounted moisture resistant luminaire. Polycarbonate body and diffuser with stainless steel diffuser retaining clips. Options: S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) H - HFR Analogue 1-10v (except 600mm versions) C - Bi-Level Dimming (Corridor Function) RLI - Reacta-Link, Wireless Enabled Luminaire RC - Reacta-Control, Wireless Enabled Luminaire LE3 - Lithium Standard Emergency 3 Hour LS3 - Lithium Selftest Emergency 3 Hour LA3 - Lithium Autotest Emergency 3 Hour TRS - Tamper Resistant Screws TRS INSTALL KIT - Tamper Resistant Compatible Screwdriver Heads

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	408 lm	LOR	100%
Luminous efficacy	136 lm/W	ULOR	4%
		Total power	3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26.6 W	CRI	80
Total flux	3154 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	4%
		Total power	26.6 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 47.24 in

Width: 3.94 in

Height: 2.95 in

Adjustability

Fixed

Electric

System power: 29.6 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

Protection

IP: 65

IK: 07

Designation labels: CE