

Product data sheet


VRT3 L295 HR
VERTECO3
DEXTRA



IP
20

Verteco 3 - IP20 Industrial Luminaire with high rack optics. Steel body white powder coated paint finish and green polycarbonate end caps. Mounting to lighting trunking using standard 20mm brass bush and locknut assembly. Side entry panel mount with female power feed plug supplied. Options: E3 - Emergency control gear (1044 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest R18H - Reacta 18, Daylight and Presence Detection Sensor, Narrow Lens R18W - Reacta 18, Daylight and Presence Detection Sensor, Wide Lens R18HRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Narrow Lens R18WRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Wide Lens

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|---------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 179.9 W | CRI | 80 |
| Total flux | 28728 lm | LOR | 100% |
| Luminous efficacy | 160 lm/W | Total power | 179.9 W |

Mounting mode

Ceiling mounted, Pendant

Electric

System power: 179.9 W

Shape and measurements

Length: 61.42 in
Width: 3.94 in
Height: 3.74 in

Protection

IP: 20

Adjustability

Fixed