


# Product data sheet

METRO GRAPHITE 360LM 2700K RA>80 TRAILING EDGE DIMMING  
7021986236934  
SG ARMATUREN



Stylishly clean wall luminaire giving attractive up and down light or just down light. Replaceable light source (included). Made of powder-coated die-cast aluminium with glass diffuser, Option of either visible or concealed connection, and connectors between wall fittings and luminaire. Wall fittings with clips for additional wiring. Light distribution Direct/Indirect Light technic LED (exchangeable) GU10 9W (2 x 4.5W) 2700K Ra>80 SDCM 4 L70/B50 >40,000 hrs Ta=25°C Control/Dimming Trailing edge dimming Protection Class II IP65 IK07 Energy and approvals A CE Materials and finish Housing: Aluminium Colour: Graphite Optics: Tempered glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block

## Light output 1



1 x LED			
Nominal lamp power	9 W	LOR	100%
Lamp flux	360 lm	ULOR	50%
Luminous efficacy	40 lm/W	Total flux	360 lm
CCT	2700 K	Total power	9 W
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 3.54 in  
Width: 5.79 in  
Height: 8.46 in

## Adjustability

Fixed

## Electric

System power: 9 W  
Appliance Class: II

## Protection

IP: 65  
IK: 07