

# Product data sheet

PLANOX  
672145.009.2.89  
RZB



Item Number: 672145.009.2.89 Series: Planox Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: plastic polycarbonate, prepared for two suspension chains or cables (suspension provided on site), interior fastening element made of sheet steel, painted white, converter integrated, refractor plastic (PMMA), opal prismatic inside, refractor attached using retaining clips made of stainless steel, with AC Control monitoring module for Luxifair central battery units. LED included. Available Colours: light grey (RAL 7035) Type of Installation: Ceiling mounting, Suspension cable/chain, Wall (surface) Dimensions: L 1573, B 96, H 100mm Lamp: LED Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: AC-Control Safety Marks: D-mark, F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 4200lm System power: 35W Beam Angle: 131°/96° Unified Glare Ratio: 23,5 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	33 W	CRI	80
Total flux	4200 lm	LOR	100%
Luminous efficacy	127 lm/W	ULOR	8%
		Total power	33 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 3.78 in  
Width: 61.93 in  
Height: 3.94 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 33 W

## Protection

IP: 66  
IK: 03