## Product data sheet

PAULA VIII 9.648.3162.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



$1\ x$ High pressure mercury vapour lamp		
Nominal lamp power	125 W	
Lamp flux	6800 lm	
Luminous efficacy	41 lm/W	
CCT	3400 K	
CRI	54	

LOR	83%
Total flux	5651 lm
Total power	137 W



1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	83%	
Lamp flux	4000 lm	Total flux	3324 lm	
Luminous efficacy	37 lm/W	Total power	89 W	
CCT	3400 K			
CRI	54			

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in Diameter: 28.74 in Electric

System power: 89-137 W

Protection

IP: 55