Product data sheet


ML26-RS40-16W-930-18°
MODULINE 26
NEKO



IP 20


Double Spotlight Inset for 48V Low Voltage System; ON-OFF Driver/0-10V Dim Driver/ DALI Dim Driver; System Power 16W; measurements Ø40mm x 70mm; high color rendering at an index of CRI90; after a lifetime of 50000h L80B10 min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 18° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work with UGR<19; degree of housing protection IP20

Light output 1 (integrated)



Lamp type	LED	CCT	2913 K
Nominal lamp power	8.02 W	CRI	92
Total flux	587 lm	LOR	100%
Luminous efficacy	73 lm/W	Total power	8.02 W

Light output 2 (integrated)



Lamp type	LED	CCT	2913 K
Nominal lamp power	8.02 W	CRI	92
Total flux	587 lm	LOR	100%
Luminous efficacy	73 lm/W	Total power	8.02 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 2.64 in
Width: 7.48 in
Height: 0.63 in

Adjustability

Rotatable, Tiltable

Electric

System power: 16.03 W

Protection

IP: 20