


Product data sheet

VOLKMAR II (WALL FITTING)
9.840.0089.05
LEIPZIGER LEUCHTEN




For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL - or DB -colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp			
Nominal lamp power	50 W	LOR	85%
Lamp flux	2000 lm	ULOR	28%
Luminous efficacy	29 lm/W	Total flux	1693 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	85%
Lamp flux	4000 lm	ULOR	28%
Luminous efficacy	38 lm/W	Total flux	3385 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in
Diameter: 16.14 in

Design

Material impression: Matt
Color of housing: White

Electric

System power: 59-89 W
Ballast: ECG
Suitable for feed-through wiring

Protection

IP: 55
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F