Product data sheet

EVA II 9.898.2036.05

LEIPZIGER LEUCHTEN






CRI




For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistent, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lampNominal lamp power50 WLamp flux3500 lmLuminous efficacy33 lm/WCCT2000 K

LOR59%ULOR14%Total flux2067 lmTotal power62 W



1 x High pressure sodium vapour lamp

• .			
Nominal lamp power	70 W	LOR	59%
Lamp flux	5600 lm	ULOR	14%
Luminous efficacy	40 lm/W	Total flux	3307 lm
CCT	2000 K	Total power	83 W
CRI	25		

25

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in Diameter: 15.75 in Electric

System power: 62-83 W

Protection

IP: 55