Product data sheet


PITTSBURGH 1 FLOODLIGHTS, PROJECTORS AND COLUMN PROJECTORS
PIB-50005-N-40
LIGMAN



IP 66 IK 08


- Lamp LED - Colour RGBW30,RGBW40 - Extruded aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Galvanized steel arm mounted - Thermal heat dissipation body - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency polycarbonate lens - Clear toughened glass - Integral control gear - Surge protection 10kV

Light output 1 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	13.5 W	CRI	-29
Total flux	883 lm	LOR	100%
Luminous efficacy	65 lm/W	ULOR	50%
		Total power	13.5 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.5 W	CRI	80
Total flux	1526 lm	LOR	100%
Luminous efficacy	87 lm/W	ULOR	50%
		Total power	17.5 W

Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	17.2 W	CRI	-50
Total flux	212 lm	LOR	100%
Luminous efficacy	12 lm/W	ULOR	50%
		Total power	17.2 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	16.6 W	CRI	-18
Total flux	1626 lm	LOR	100%
Luminous efficacy	98 lm/W	ULOR	50%
		Total power	16.6 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 8.94 in
Width: 20.87 in
Height: 3.54 in
Weight: 6.5 kg

Adjustability

Fixed

Electric

System power: 64.8 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C