



# Product data sheet

EASY KAP 105  
03.4456.B1/Hi PAR 51/35W/10°25°40°  
FLOS




Luminaire for recessed mounting on ceilings for halogen, metal halide and LED lamps. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).


## Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	70%
Luminous efficacy	42 lm/W	Total flux	1460 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	67%
Luminous efficacy	40 lm/W	Total flux	1412 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	69%
Luminous efficacy	42 lm/W	Total flux	1457 lm
CCT	3000 K	Total power	35 W
CRI	84		

## Mounting mode

Ceiling recessed

## Electric

System power: 35 W

### Shape and measurements

Height: 6.38 in

Diameter: 4.13 in

### Adjustability

Fixed

### Protection

IP: 20