


Product data sheet

PH LOUVRE LED 2700K 96W
5741094655
LOUIS POULSEN



PH Louvre Design : Poul Henningsen Light concept : The fixture provides 100% glare-free light. The geometrical, spherical design is based on the principle of illuminating all surfaces at the same angle. This ensures uniform light around the fixture, illuminating both walls and ceiling. Matte painted undersurfaces and glossy top surfaces result in an attractive reflection of the diffused light, creating uniform light distribution around the fixture. Finish: White, wet painted. Material: Shades: Spun aluminium. Frame: High lustre chrome plated, extruded brass. Housing: High lustre chrome plated, spun aluminium. Mounting: Suspension type: Cable 3x0,75mm² & wire. Canopy: Yes. Cable length: 4m. Weight: Max. 7kg. Class: Ingress protection IP20. Electric shock protection I w. ground.

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	96 W	CRI	90
Total flux	2740 lm	LOR	100%
Luminous efficacy	29 lm/W	ULOR	18%
		Total power	96 W

Mounting mode

Pendant

Shape and measurements

Height: 25.59 in

Diameter: 23.62 in

Adjustability

Fixed

Electric

System power: 96 W

Appliance Class: I

Protection

IP: 20