


Product data sheet

LOUI 50
925340.0045.1.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50;system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Colour: silver, matt (approx. RAL9006) Length: 1961mm Width: 71mm Height: 1.5mm Cut-out length: 1968mm Cut-out width: 60mm Recess height: 100mm Luminaire: recess height: 75mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 47W Rated luminous flux: 5650lm Luminous efficiency: 120lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	47 W	CRI	80
Total flux	5650 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	47 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 77.20 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 47 W

Protection

IP: 20
IK: 03