Product data sheet


GLOB PÄRLAN 400 3K AKRYL STÅNG
E7509747
CARDI



IP 20


Klassisk pendelarmatur i stilren design, där LED-modulen lyser upp hela globen och ger ett mjukt och jämt ljus. Glob Pärlan ger ett arkitektoniskt inslag som passar de flesta applikationer och ger möjlighet att skapa och bygga spännande inredningselement. Globen finns i olika storlekar för att passa olika rum och behov. LED-modulen har ställbart ljusflöde och ställbar position vilket gör det möjligt att justera dess ljusmängd och position i förhållande till globens storlek, detta gör att ljuset kan fördelas jämnt över globens yta och skapa en enhetlig belysning oavsett diameter på globen. Förinställt värde är det ljusflöde vi rekommenderar för Glob Pärlan Ø400mm. Fast pendelrör och takkkopp av mattvit pulverlackerat stål, glob av matt opal akryl. Längd pendelrör inkl. takkopp 677 mm. Pendelröret går att kapa. Insticksplint 3x2x2,5 mm².

Light output 1




1 x LED

Nominal lamp power	22 W	LOR	100%
Lamp flux	3630 lm	ULOR	7%
Luminous efficacy	165 lm/W	Total flux	3630 lm
CCT	3000 K	Total power	22 W
CRI	80		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2430 lm	ULOR	7%
Luminous efficacy	122 lm/W	Total flux	2430 lm
CCT	3000 K	Total power	20 W
CRI	80		




1 x LED

Nominal lamp power	19 W	LOR	100%
Lamp flux	2240 lm	ULOR	7%
Luminous efficacy	118 lm/W	Total flux	2240 lm
CCT	3000 K	Total power	19 W
CRI	80		




1 x LED

Nominal lamp power	17 W	LOR	100%
Lamp flux	2030 lm	ULOR	7%
Luminous efficacy	119 lm/W	Total flux	2030 lm
CCT	3000 K	Total power	17 W
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1820 lm	ULOR	7%
Luminous efficacy	121 lm/W	Total flux	1820 lm
CCT	3000 K	Total power	15 W
CRI	80		




1 x LED

Nominal lamp power	13 W	LOR	100%
Lamp flux	1600 lm	ULOR	7%
Luminous efficacy	123 lm/W	Total flux	1600 lm
CCT	3000 K	Total power	13 W
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3160 lm	ULOR	7%
Luminous efficacy	113 lm/W	Total flux	3160 lm
CCT	3000 K	Total power	28 W
CRI	80		




1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	2810 lm	ULOR	7%
Luminous efficacy	117 lm/W	Total flux	2810 lm
CCT	3000 K	Total power	24 W
CRI	80		




1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3320 lm	ULOR	7%
Luminous efficacy	111 lm/W	Total flux	3320 lm
CCT	3000 K	Total power	30 W
CRI	80		




1 x LED

Nominal lamp power	11.5 W	LOR	100%
Lamp flux	1380 lm	ULOR	7%
Luminous efficacy	120 lm/W	Total flux	1380 lm
CCT	3000 K	Total power	11.5 W
CRI	80		




1 x LED

Nominal lamp power	26 W	LOR	100%
Lamp flux	2980 lm	ULOR	7%
Luminous efficacy	115 lm/W	Total flux	2980 lm
CCT	3000 K	Total power	26 W
CRI	80		




1 x LED

Nominal lamp power	39 W	LOR	100%
Lamp flux	3980 lm	ULOR	7%
Luminous efficacy	102 lm/W	Total flux	3980 lm
CCT	3000 K	Total power	39 W
CRI	80		




1 x LED

Nominal lamp power	37.5 W	LOR	100%
Lamp flux	3860 lm	ULOR	7%
Luminous efficacy	103 lm/W	Total flux	3860 lm
CCT	3000 K	Total power	37.5 W
CRI	80		




1 x LED

Nominal lamp power	35.5 W	LOR	100%
Lamp flux	3740 lm	ULOR	7%
Luminous efficacy	105 lm/W	Total flux	3740 lm
CCT	3000 K	Total power	35.5 W
CRI	80		



1 x LED

Nominal lamp power	33.5 W	LOR	100%
Lamp flux	3600 lm	ULOR	7%
Luminous efficacy	107 lm/W	Total flux	3600 lm
CCT	3000 K	Total power	33.5 W
CRI	80		



1 x LED

Nominal lamp power	32 W	LOR	100%
Lamp flux	3460 lm	ULOR	7%
Luminous efficacy	108 lm/W	Total flux	3460 lm
CCT	3000 K	Total power	32 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 15.75 in
Width: 15.75 in
Height: 15.83 in

Adjustability

Fixed

Electric

System power: 11.5-39 W
Appliance Class: I

Protection

IP: 20