

Product data sheet

814 3000K CRI 90 24W CLD SILVER
150360-39
DISANO



Housing: injection molded in self-extinguishing polycarbonate in RAL9016 colour. Accessory compartment made of white-painted 7/10-thick steel sheet. Optics: secondary lenses in high-performance and anti-yellowing PMMA. : UGR<lt/>16 (up to 24W) - UGR<lt/>19, according to standard EN 12464. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: Comfortsquare (19-1928) comes as standard with a presence/light sensor that switches the ceiling fixture on or off whenever it detects presence within its scan range and depending on the amount of the light in the space.

Light output 1



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	2992 lm	Total flux	2992 lm
Luminous efficacy	125 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 1.65 in

Adjustability

Fixed

Design

Color of housing: Silver gray, White

Electric

System power: 24 W
Appliance Class: I

Protection

IP: 43
IK: 07
Designation labels: CE, ENEC