Product data sheet


VARIOPLAST I
672126.002.04
RZB



IP 65 IK 08


Series: VARIOPLAST I Luminaire for escape route identification. Base: plastic (polycarbonate). Housing and diffusor: opal, made of shockproof plastic (polycarbonate). 4 plastic foils with escape route motifs included (ISO 7010). Self-contained system with automatic self-test and feedback to the RZB monitoring system MULTIDIGIT. Luminaire with limited surface temperature in accordance with EN 60598-2-24 for use in environments in which a deposit of conductive dust on the luminaire can be expected. Ball impact proof in accordance with DIN 18032-3. Qualified for use in the food and drink industry. Colour: white Length: 320 mm Width: 80 mm Height: 186 mm Weight: 1.03 kg Operating mode: maintained power mode Viewing Distance: 24 m Duration time: 3 h Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 4.3 W Rated luminous flux: 200 lm Luminous flux, emergency: 70 System power, emergency: - Control gear: Regulated power supply Protection class: I Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.3 W	CRI	80
Total flux	200 lm	LOR	100%
Luminous efficacy	47 lm/W	ULOR	15%
		Total power	4.3 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.3 W	CRI	80
Total flux	70 lm	LOR	100%
Luminous efficacy	16 lm/W	ULOR	15%
		Total power	4.3 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.15 in
Width: 12.60 in
Height: 7.32 in

Electric

System power: 8.6 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 65

IK: 08