# Product data sheet

#### **NATIONS**

#### EVO2 NATIONS-ASY27-32LED-1700K-500 MA

RAGNI










The LED module is specially designed to replace traditional asymmetrical road reflectors. It is composed of a die-cast aluminium heat sink, a tempered glass cover and a cellular silicone gasket. The module is available in a sealed version (IP 66) with pressure regulating vent. Its impact resistance index is IK 08. Electrical class II, it receives from 8 to 64 LEDs @ 700 mA, and offers multiple color temperatures and light distributions. The module can be coupled to a management system to adapt lighting to needs and save energy. Equipped with a passive finned heatsink located behind the PCB, it is in contact with the luminaire body to improve thermal conduction. It is also equipped with a cable gland. Driver and PCB to Zhaga standards (Zhaga book 13, 15), the module is compatible with almost all of our luminaires. Its ULR is 0% and it is EEC eligible (case n°1), in accordance with the requirements of the NF EN 13201 standard and RoHs requirements.

#### Light output 1



1	Χ	LED
Λ	loi	minal

Nominal lamp power 46.9 W
Lamp flux 4308 lm
Luminous efficacy 92 lm/W
CCT 1700 K
CRI 80

LOR Total flux

Total power

100% 4308 lm 46.9 W

# Mounting mode

Pole top mounted

# Shape and measurements

Length: 19.69 in Width: 11.81 in Height: 3.94 in

### Adjustability

Fixed

# Electric

System power: 46.9 W Appliance Class: II

## Protection

IP: 66 IK: 08