
Product data sheet


SINUS CURVED SEGMENT DI/ID BLACK PRISM. 90° R920
P33-H49-9005E2840H3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


high output LED 4000K CRI 90 67,2W 7887lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 13,1% https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.2 W	CRI	90
Total flux	1315 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	11.2 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.2 W	CRI	90
Total flux	1315 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	11.2 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.2 W	CRI	90
Total flux	1315 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	11.2 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.2 W	CRI	90
Total flux	1315 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	11.2 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11.2 W	CRI	90
Total flux	1315 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	11.2 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11.2 W	CRI	90
Total flux	1315 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	11.2 W

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 37.60 in

Width: 37.60 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 67.2 W

Protection

IP: 40