


Product data sheet

SL720+ PL RXL 61 S/C 840 GR9006 SEIR MP
3115942
PERFORMANCE IN LIGHTING



Suspended, LED luminaire for indoor, comprising: Extruded aluminium housing profile, powder-coated. Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP). LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover. Easy, subsequent replacement of the LED modules in just a few simple steps (can also be carried out without an electrician). Direct. Indirect light distribution. Colour rendering index Ra > 80. Colour tolerance according to MacAdam ≤ 3 SDCM. Dimmable via TouchDIM®. With the "OSRAM BT Control" Bluetooth control, the light can be easily configured, personalised or grouped via the app using various parameters. In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8). In the HCL version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8). Sensor device available with task oriented PIR detector and daylight control. Complete with steel suspension cable (1.5 m), transparent power cord and canopy. VDU application suitable acc. to EN 12464-1. Special colour versions available. Consult factory.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	69 W	CRI	80
Total flux	9008 lm	LOR	100%
Luminous efficacy	131 lm/W	ULOR	5%
		Total power	69 W

Mounting mode

Pendant

Shape and measurements

Length: 60.55 in

Width: 9.45 in

Height: 0.79 in

Design

Color of housing: Silver gray

Electric

System power: 69 W

Appliance Class: I

Protection

IP: 20