## Product data sheet

LUCAS VIII (WALL FITTING BEADED) 9.828.2072.16

LEIPZIGER LEUCHTEN








High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



## $1\,\mathrm{x}$ High pressure sodium vapour lamp

3 1	- I I		
Nominal lamp power	150 W	LOR	80%
Lamp flux	17000 lm	ULOR	4%
Luminous efficacy	77 lm/W	Total flux	13598 lm
CCT	2000 K	Total power	176 W
CRI	25		

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 176 W

Protection

IP: 55