


Product data sheet

FLC220 [GP] IP66:LED-FT-37W/4K - MIN APERTURE ANGLE
139-2124
WE-EF



Profile Projector [FP] for framing applications, polygon shape. Spherical/triple flat convex lens system. Profile Projector [GP] for projection of gobos on a surface. Spherical/triple flat convex lens system. Gobo motif on request, to be ordered separately. Profile Projector [ZP] for zoom spot. Spherical/triple flat convex lens system. IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. PMMA LED lens array. Factory installed LED circuit board. LED board can be removed for upgrading. Integral EC electronic converter, thermally separated.

Light output 1



1 x LED			
Nominal lamp power	37 W	LOR	69%
Lamp flux	4900 lm	Total flux	3387 lm
Luminous efficacy	81 lm/W	Total power	42 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Height: 1.18 in
Diameter: 1.18 in
Weight: 8.2 kg

Electric

System power: 42 W
Appliance Class: I

Protection

IP: 66
IK: 07