


Product data sheet

RBX*FL 126 L90 E3
RUBIX FLUSH LED EMERGENCY
DEXTRA




Rubix Flush - 1200x600 Recessed luminaire, white powder coated steel body, individual cells with opal surround trim for precise optical control. Replace * with P for Pull-up or R for Lay-in. Options: E3 - Emergency control gear (422 lumens output) ST3 - Emergency control gear self test AT3 - Emergency control gear DALI auto test S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence BL - Blue Cell Surround OR - Orange Cell Surround R - Red Cell Surround BK - Black Cell Surround AH25 - Air handling 25 litres per second

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	54.5 W	CRI	80
Total flux	7188 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	4%
		Total power	54.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.8 W	CRI	80
Total flux	422 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	4%
		Total power	3.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.24 in

Width: 23.62 in

Height: 2.09 in

Electric

System power: 58.3 W

Ballast: ECG

Protection

IP: 20

Designation labels: CE

Adjustability

Fixed