


Product data sheet

PURE 3 DOWNLIGHT
09.1810/QR-111/100W/8°24°45°
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	977 lm	LOR	103%
Luminous efficacy	10 lm/W	Total flux	1002 lm
CCT	3000 K	Total power	100 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1368 lm	LOR	100%
Luminous efficacy	14 lm/W	Total flux	1370 lm
CCT	3000 K	Total power	100 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1089 lm	LOR	100%
Luminous efficacy	11 lm/W	Total flux	1091 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Ceiling recessed

Electric

System power: 100 W
Appliance Class: III

Shape and measurements

Length: 5.91 in

Width: 5.91 in

Height: 5.51 in

Adjustability

Rotatable, Tilttable

Protection

IP: 20