



# Product data sheet

IQ SUSP S LED4900-830 HF ML3  
96629280  
THORN LIGHTING



A lightweight, suspended, LED luminaire with MV Tech optic. Electronic, fixed output control gear. Class I electrical, IP20, IK05. Body, diffuser, frame and endcaps: polycarbonate (Tpa) finished in white (close to RAL9016). Gear tray: pre-coated white steel. Fitted with 3 core cable. Complete with 3000K LED Dimensions: 1140 x 210 x 70 mm Total power: 42 W Luminaire luminous flux: 4600 lm Luminaire efficacy: 110 lm/W weight: 4.3 kg

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	80
Total flux	4600 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	22%
		Total power	42 W

## Mounting mode

Pendant

## Shape and measurements

Length: 44.88 in  
Width: 8.27 in  
Height: 2.76 in  
Weight: 4.3 kg

## Design

Material impression: Plastic  
Color of housing: White

## Electric

System power: 42 W  
Voltage: 220-240 V AC  
Appliance Class: I

## Protection

IP: 20  
IK: 05  
Designation labels: CE