Product data sheet

CRUISER 2 LB LED ED 88W 13650LM 4000K GRAY - HIGH EFFICACY FOR INTERNAL MOUNTING 300092.00185

LUG










Industrial luminaire for LED light sources. Mounting: surface mounted, in the ceiling, with mounting frame (sold separately), suspended, on chains (on request), for hanging on a cable, with special mounting bracket (on request) Body: high pressure die-cast aluminum Power: 220-240V 50/60Hz Lifetime (L80B10): 100 000 h Lifetime (L90B10): 50 000 h Additional information: Ball impact resistance. The possibility of using one or more power supplies in the luminaire. Other remarks: Beam angle: 100° Warranty: 3 years Application: warehouses, logistics centers, industrial facilities, sport facilities, roofing

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	88 W	CRI	80
Total flux	13650 lm	LOR	100%
Luminous efficacy	155 lm/W	Total power	88 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 20.28 in Width: 13.58 in Height: 3.54 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 88 W Appliance Class: I

Protection

IP: 66 IK: 07

Resistant to impact of balls