


# Product data sheet

ORION WHITE 800LM 3000K RA>80 TRAILING EDGE DIMMING  
7021982121104  
SG ARMATUREN



Attractive, round LED wall/ceiling luminaire for indoor mounting. Made of painted metal. Diffuser made of UV-stabilised opal polycarbonate. Efficient LED board with long service life. Hatch for easy access to connection, and option of both visible and concealed cabling as well as loopable quick clips. Vandal-resistant rating IK10. Light distribution Direct Light technic LED 10W 3000K Ra>80 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP20 IK10 Materials and finish Housing: Steel Colour: White Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor Screwless terminal block

## Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	100%
Lamp flux	800 lm	ULOR	21%
Luminous efficacy	80 lm/W	Total flux	800 lm
CCT	3000 K	Total power	10 W
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 11.85 in

Width: 11.85 in

Height: 3.43 in

## Adjustability

Fixed

## Electric

System power: 10 W

Appliance Class: II

## Protection

IP: 20

IK: 10