

Product data sheet

CUBIC EVOLUTION SUSPENDED - G6
CG6OEE-840M-Q300-K
LIGHTNET



LED pendant luminaire. Direct-indirect or direct--only light distribution. Luminaire body with minimalistic overall height made of aluminium profile. Surface natural anodised or white, graphite, black or champagne coated as well as polished aluminium. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Indirect light with innovative lens technology for wide-angle ceiling illumination. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperature 2700K, 3000K, 3500K or 4000K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable parallel-cord suspension with transparent power supply cable.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11 W	CRI	82
Total flux	1210 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	11 W

Mounting mode

Pendant

Shape and measurements

Length: 11.81 in
Width: 11.81 in
Height: 0.98 in

Adjustability

Height adjustable

Electric

System power: 11 W

Protection