

Product data sheet

LED IT STRIP
982521.002.1
RZB



IP
65

Series: LED it Strip Type of Protection: IP 65 Voltage: 24 V / 0 Hz Flexible fully encapsulated LED strip for indoor and outdoor use. UV/IR resistant TPU potting. Solderless connection technology by means of plug &Play connector system. Easy separability with commercially available tools. every 250 mm. Up to 20 meters LED strip length with only one power supply. Supply voltage 24 V DC, 4 W/m, 400 lm/m (370 lm/m at 3000 K). 7 LEDs per segment, LED pitch 35.7 mm. Smallest bending radius 60 mm. Operating temperature from -20 °C to 50 °C. One power supply and one End cap included, other accessories can be ordered separately. Available Colours: white Dimensions: L 20000, B 12, H 3
Lamp: LED Life time: 35000 h Colour Temperature: 4000K Socket 1: without socket Luminaire flux LED: 8000lm System power: 80W Beam Angle: 110° Unified Glare Ratio: 22,5

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	80 W	CRI	80
Total flux	8000 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	80 W

Mounting mode

Wall mounted

Shape and measurements

Length: 0.47 in
Width: 39.37 in
Height: 0.16 in

Adjustability

Fixed

Electric

System power: 80 W

Protection

IP: 65