
# Product data sheet


SINUS CURVED SEGMENT DI SILVER PRISM. 45° R552
P33-A14-9006E1840L3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


low output LED 4000K CRI 90 6,6W 692lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,4% https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 3.3 W | CRI | 90 |
| Total flux | 346 lm | LOR | 100% |
| Luminous efficacy | 105 lm/W | Total power | 3.3 W |

## Light output 2 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 3.3 W | CRI | 90 |
| Total flux | 346 lm | LOR | 100% |
| Luminous efficacy | 105 lm/W | Total power | 3.3 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 16.34 in
Width: 8.70 in
Height: 3.94 in

### Adjustability

Fixed

### Electric

System power: 6.6 W

### Protection

IP: 40