


Product data sheet

SHIFT 26-500S-50GGE/940, B
26-500S-50GGE/940
HALLA




26-500S-50GGE/940, B Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Rounded Size: 1020 x 85 x 92 mm
Type of installation: Suspended Distribution: Direct Optics type: Reflector Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.3 W	CRI	90
Total flux	1810 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	17.3 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.3 W	CRI	90
Total flux	1810 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	17.3 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.3 W	CRI	90
Total flux	1810 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	17.3 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17.3 W	CRI	90
Total flux	1810 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	17.3 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17.3 W	CRI	90
Total flux	1810 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	17.3 W

Mounting mode

Pendant

Shape and measurements

Height: 2.36 in
Diameter: 3.35 in

Adjustability

Rotatable, Tilttable

Electric

System power: 86.5 W
Appliance Class: I

Protection

IP: 20