Product data sheet

THINDR 1747.AS.7

PSM LIGHTING









built-up ceiling light - fixed - feeding asymmetric - with LED driver

Light output 1 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 2 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 3 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 4 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total pow	er 3.8 W

Light output 5 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 6 (integrated)



Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 7 (integrated)



Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.49 in Width: 1.77 in Height: 35.83 in

Electric

System power: 26.6 W Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Adjustability

Fixed

Design

Material impression: Matt Color of housing: Other colors Designer: Saskia Mortier Protection

IP: 20

IK: 02