

Product data sheet


ATLANTYK 2.0 BASIC LED 1245 DALI + THROUGH WIRING (TW) 5X1,5 MM² 40W 5900LM 4000K POLYCARBONATE IP65 G.. 090380.3L04.021.938

LUG



Hermetic LED luminaire, water-jet proof, intended for mounting inside industrial or architectural objects. Luminare with Easy Connect.
Mounting: directly on the ceiling, with mounting brackets (included), suspended, on chains, on wire suspension (on request) Body: plastic
Power: 220-240V 50/60Hz Lifetime (L80B10): 100 000 h Available on request: available with connection to a central battery power supply, radar motion detector, twilight sensor Warranty: 5 years Application: parking areas, production halls, warehouses, assembly halls, warehouses, electricity plants, mills, workshops, wood and paper industry Type of optics: opal diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40 W	CRI	80
Total flux	5900 lm	LOR	100%
Luminous efficacy	148 lm/W	ULOR	9%
		Total power	40 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 49.02 in

Width: 3.94 in

Height: 3.54 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite

Electric

System power: 40 W

Controller: DALI

Appliance Class: I

Protection

IP: 65

IK: 08