


# Product data sheet

TENTEC ACCENT RECESSED LUMINAIRE, SAFETY SCREEN  
TL2102501-30-40 + 83817Q08-60\_5W  
SCHMITZ | WILA



Tentec accent LED 4000 K Recessed Luminaire, Light distribution direct Downlight with lite optic Safety Screen Product: TL2102501-30-40  
Operating technology: independent driver required Lite Optic: 83817Q08-60 Lite Optic Safety Screen Tempered safety glass Aluminium reflector (Al99.98), high-polished Half-peak divergence  $\alpha = 60^\circ$  Light Technique CRI > 80 High chromaticity stability with 3SDCM (initial) Constant colour temperature 4000 K Lifetime 50.000 h (L70) Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2 mm for homogeneous appearance in the ceiling frame colour white, RAL 9016  
Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 5 W Colour Rendering Index: 80 Colour Temperature: 4000 K Luminaire Luminous Flux: 640 Llm System Efficiency: 107 Llm/W Half-peak Divergence  $\alpha = 60^\circ$  Number Luminaires LZ: 0.19 Connector: screw connector, 2 x 2.5 mm2 Reflector Size: Q08 Length: 102 mm Width: 102 mm Cut-out length: 95 mm Cut-out width: 95 mm Installation Depth RD: 110 mm Total Weight: 0.6 kg Degree of Protection IP44, IP44 in closed ceiling systems CE-Sign Total system: Protection class 2 Data record TL2102501-30-40+83817Q08-60\_5W

## Light output 1



### 1 x General service incandescent lamp

Nominal lamp power	6 W	LOR	100%
Lamp flux	640 lm	Total flux	640 lm
Luminous efficacy	107 lm/W	Total power	6 W
CCT	4000 K		
CRI	80		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 4.02 in  
Width: 4.02 in  
Height: 4.33 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 6 W  
Appliance Class: II

## Protection

IP: 44