Product data sheet

LIGHT EYE® 1PH., QPAR51
1008170
SLV



IP 20

The popular spotlights and pendant lights for the 1- and 3-phase system extend the LIGHT EYE® family with new elegant models. Available in diameters of 90 and 150 mm, they offer a stylish design that shines with a sophisticated matt look. The separately available and interchangeable decorative rings create a modern look with their trendy colours.

Light output 1



1 x LED

Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	100%
Luminous efficacy	75 lm/W	Total flux	450 lm
CCT	2723 K	Total power	6 W
CRI	92		



1 x LED

Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	100%
Luminous efficacy	75 lm/W	Total flux	450 lm
CCT	3058 K	Total power	6 W
CRI	92		



1 x LED

Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	100%
Luminous efficacy	75 lm/W	Total flux	450 lm
CCT	4033 K	Total power	6 W
CRI	93		

Mounting mode

Ceiling mounted, Contact rail

Electric

System power: 6 W

Shape and measurements

Length: 39.37 in

Width: 39.37 in

Height: 39.37 in

Weight: 0.272 kg

Adjustability

Fixed

Protection

IP: 20