


Product data sheet

VISION SURFACE - A2
VA20EE-840M-L1182
LIGHTNET



LED surface-mounted luminaire. Direct only light distribution. Light channel made of aluminium profile with 130mm width. Precise length production according to specifications possible. Surface natural anodised or white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen and satin louver for office purposes. Opal diffuser made of acrylic glass for general lighting. Wallwasher for homogeneous vertical illuminance. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	42 W	CRI	82
Total flux	4050 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	42 W

Mounting mode

Ceiling mounted

Electric

System power: 42 W

Shape and measurements

Length: 46.54 in

Width: 5.12 in

Height: 2.17 in

Protection

Adjustability

Fixed