

Product data sheet


MULTILUME FLAT DELTA TW 300X1200 CLO
23994
FAGERHULT




IP
44

Installation Recessed mounting in ventilated or unventilated suspended ceilings. Two optional designs. VTB - for suspended ceilings with visible T-bars 25 mm. 300x300 also for fixed suspended ceilings. HB - for suspended ceiling with concealed T-bars. Supplement with fixing brackets for fixed suspended ceiling, see accessories. The luminaire must not be covered with insulation. For further details please refer to the assembly instructions on our website Connection section in ballast box. The ballast box can be detached and positioned next to the luminaire. Snap-in terminal block 3x1,5?mm² (5x1,5?mm² where dimming is required). Through-wiring possible for 600x600. Design Luminaire body in white enamelled sheet steel (RAL 9016). Louvre Delta - microprism louvre in acrylic (PMMA) with a thin opal diffuser (acrylic/PMMA) on the inside (PMMA). Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.


Light output 1



1 x LED			
Nominal lamp power	47 W	LOR	100%
Lamp flux	4550 lm	Total flux	4550 lm
Luminous efficacy	97 lm/W	Total power	47 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	47 W	LOR	100%
Lamp flux	4232 lm	Total flux	4232 lm
Luminous efficacy	90 lm/W	Total power	47 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	47 W	LOR	100%
Lamp flux	4323 lm	Total flux	4323 lm
Luminous efficacy	92 lm/W	Total power	47 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.09 in

Width: 11.65 in

Height: 2.05 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 47 W

Color adjustable

Protection

IP: 44