


# Product data sheet

TANGO 37 CYLINDRICAL POST TOP LUMINAIRES  
TA-20021-W-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Extruded aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass lens - Maximum wind load resistance is 140 km/h

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4032 K |
| Nominal lamp power | 38.5 W   | CRI         | 80     |
| Total flux         | 3883 lm  | LOR         | 100%   |
| Luminous efficacy  | 101 lm/W | Total power | 38.5 W |

## Light output 2 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4032 K |
| Nominal lamp power | 38.5 W   | CRI         | 80     |
| Total flux         | 3883 lm  | LOR         | 100%   |
| Luminous efficacy  | 101 lm/W | Total power | 38.5 W |

## Mounting mode

Standing / Bollard, Pole top mounted

## Shape and measurements

Height: 25.59 in  
Diameter: 7.32 in  
Weight: 23.5 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 77 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C