


# Product data sheet

3-PH LINEAR LIGHT 600MM, 20W, 110°, WHITE MATT, 3000K


113021

ISOLED



3-PH linear luminaire 600mm, 20W, 110°, matt white, 3000K - HV LED Track light incl. 3-PH EURO adapter, gapless light line possible | Dimensioned wattage: 20 W | Effective wattage: 20 W | Energy efficiency class: E (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Material: cast aluminum | Surface color: white matt | Protection class: IP20 | Suitable for indoor use only | Allowable ambient Temperatures: -20° - 40° C | Beam angle: 110° fixed | Color temperature: 3000K | Color rendering index: 90 (Ra 1-8) | Luminous flux: 2200 lm | Usable service life: 68000 h (L80|B50) | Warranty: 3 years | Special features: incl. 3-PH EURO adapter, seamless light line possible by stringing together individual modules | FABRICATION: ISOLED 113021

## Light output 1



### 1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2200 lm	ULOR	17%
Luminous efficacy	110 lm/W	Total flux	2200 lm
CCT	3000 K	Total power	20 W
CRI	90		

## Mounting mode

Ceiling mounted, Contact rail, Contact rail

## Shape and measurements

Length: 23.82 in

Width: 1.26 in

Height: 2.32 in

## Adjustability

Fixed

## Design

Material impression: Aluminum

Color of housing: White

## Electric

System power: 20 W

Ballast: ECG

## Protection

IP: 20

Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...104°F