


Product data sheet

SLOIN T SL IP54 LED2000-840 L1563 WW
42185618
ZUMTOBEL



LED light line in IP54 with DALI-controllable LED converter; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 2090 lm, Luminaire efficacy: 84 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire of aluminium, white powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate including integrated reflector for asymmetric light distribution. For installing in module ceilings with 12 mm edges and for installing in plasterboard ceilings. Armstrong® TECH ZONE compatible with ceiling types with width 100 mm. Includes gear tray, reflectors, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP54. Dimensions: 1563 x 100 x 134 mm weight: 5.1 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24.8 W	CRI	80
Total flux	2090 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	24.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 61.54 in
Width: 3.94 in
Height: 5.28 in
Weight: 5.1 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 24.8 W
Voltage: 220-240 V AC
Controller: DALI

Protection

IP: 54