


Product data sheet

GLAC2 S LED2 1000-840 HFIX EC GY GL PR
96629702
THORN LIGHTING



A modern and efficient LED pendant luminaire. DALI dimmable control gear suitable for central battery emergency installations. Housing: die-cast aluminium with satin grey finish. Reflector: prismatic glass with easy bayonet mount connection to housing. Class I electrical, IP20. Suspended via adjustable quick-lock 2.5m single wire suspension (supplied). Pre-wired with braided, flame retardent silicon cable, 5 x 0.75mm². Complete with 4000K LED Dimensions: Ø250/100 x 370 mm Total power: 8.5 W Weight: 3.6 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8.5 W	CRI	80
Total flux	1050 lm	LOR	100%
Luminous efficacy	124 lm/W	ULOR	5%
		Total power	8.5 W

Mounting mode

Pendant

Shape and measurements

Length: 9.84 in

Width: 3.94 in

Height: 14.57 in

Weight: 3.6 kg

Design

Material impression: Aluminum

Electric

System power: 8.5 W

Voltage: 220-240 V AC

Controller: DALI

Appliance Class: I

Protection

IP: 20

Designation labels: CE, ENEC