


Product data sheet

MATRIC 55MM WALL DIRECT-INDIRECT - W4
LW4AEG-840M-L890
LIGHTNET



LED wall mounted luminaire. Direct-indirect light distribution. Light channel made of aluminium profile with 55mm profile width. Precise length production according to specifications possible. Surface natural anodised or white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting. Driver integrated into luminaire housing, optionally separately switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	33 W	CRI	82
Total flux	3620 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	52%
		Total power	33 W

Mounting mode

Wall mounted

Electric

System power: 33 W

Shape and measurements

Length: 35.04 in

Width: 2.17 in

Height: 4.92 in

Protection

Adjustability

Fixed