



# Product data sheet

LD34 13.2W 350MA MB  
LD34-C1-350-75-MB-900  
LIGHTGRAPHIX



LD34 Recessed linear wall grazer. IP67. Constant Current 13.2W 350mA 31° Medium beam. The LD34 is a low glare, shallow recessed, in-ground, linear wall grazer which offers outstanding continuous wall washing capabilities for interior and exterior projects. It features a fixed 2.5° tilt, integral glare control options and individual cowls over each LED to ensure low glare from the viewer's perspective. Multiple colour temperatures and beam angles are available, as well as accessories including an optional frosted diffusion filter to illuminate even the lowest parts of the wall. With multiple set lengths and a compact design, this high-power solution will integrate into harsh environments ensuring long lasting reliability, excellent thermal and light output performance.

## Light output 1



1 x LED			
Nominal lamp power	13.2 W	LOR	100%
Lamp flux	1023 lm	ULOR	98%
Luminous efficacy	78 lm/W	Total flux	1023 lm
CCT	3000 K	Total power	13.2 W
CRI	93		

## Mounting mode

Floor recessed

## Shape and measurements

Length: 36.14 in  
Width: 2.64 in  
Height: 1.97 in

## Adjustability

Fixed

## Design

Material impression: Glass, Gloss, Matt, Stainless steel  
Color of housing: Black, White, Anthracite / graphite, Silver gray

## Electric

System power: 13.2 W  
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI  
Appliance Class: III

## Protection

IP: 67  
IK: 08  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...113°F