Product data sheet


LINEA S LED ECO 1764MM 7550LM 840 IP40 SA-R (45W)
594786
LENA LIGHTING



IP 40 IK 03

594786 LINEA S LED ECO 1764mm 7550lm 840 IP40 SA-R (45W) Linea S LED Eco is a surface-mounted and pendant light-line system, representing a new generation of luminaires dedicated to LED technology. The design used allows for easy installation and power connection. The steel body, designed from the ground up, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. The ECO version is dedicated to investments where the length of individual light lines supplied from a single cable (not including modules with bezels and not including current protection) does not exceed 40m. The light modules are permanently connected to the carrier modules using dedicated cubes. The optics used in the other luminaires of the LINEA S family are possible.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	45 W	CRI	80
Total flux	7550 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	45 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 69.45 in
Width: 1.97 in
Height: 2.56 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 45 W
Ballast: ECG
Appliance Class: I

Protection

IP: 40
IK: 03

Other operating numbers

Ambient temperature range: -4...95°F