


Product data sheet

RONDOS
911205.003.76
RZB



Series: Rondos Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Housing: powder coated die cast aluminium. Cold extruded aluminium heat sink. Passive cooling. Rotates 178° and swivels ± 35°. Installation without tools thanks to spring fastening system. Heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools. LED included. Connected converter included in separate gearbox. Available Colours: deep black, matt (RAL 9005) Type of Installation: Recessed ceiling mounting Dimensions: D 157, H 6, HE 180 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 2700K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 2550lm System power: 25W Beam Angle: 15° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 17,7 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	25 W	CRI	80
Total flux	2550 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	25 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.04 in
Diameter: 6.18 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Black

Electric

System power: 25 W

Protection

IP: 20
IK: 02