



Product data sheet

PRODISC II MAXI Ø 400 MM
40009461
PROLUMIA




Light source: SMD 2835 LED Beam angle: 120° Color temperature: 3000K (Warm white), 4000K (Pure white) Light output: 2800Lm/3000Lm
Light output emergency mode: 280Lm/300Lm Operating temperature: -20°C - +50°C Rated life hours: > 50,000 LED driver (included): CE Input:
220-240V AC 50/60Hz Wiring class: Class II Power factor: > 0.90 Autonomy:1 hour


Light output 1




1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2000 lm	Total flux	2000 lm
Luminous efficacy	100 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	3000 lm	Total flux	3000 lm
Luminous efficacy	100 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		




1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2000 lm	Total flux	2000 lm
Luminous efficacy	100 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1500 lm	Total flux	1500 lm
Luminous efficacy	100 lm/W	Total power	15 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3000 lm	Total flux	3000 lm
Luminous efficacy	100 lm/W	Total power	30 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1500 lm	Total flux	1500 lm
Luminous efficacy	100 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	280 lm	Total flux	280 lm
Luminous efficacy	9 lm/W	Total power	30 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	300 lm	Total flux	300 lm
Luminous efficacy	10 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Height: 4.21 in

Diameter: 15.75 in

Electric

System power: 15-30 W

Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

Protection

IP: 44

IK: 08

Designation labels: CE