



Product data sheet

LINEAR XL OPTION UPLIGHT - RGBW - MILKY - 1174MM
 L9XU11M0
 PROLED (MBN GMBH)




The option Uplight RGBW for the LINEAR XL luminaire series has to be orderd in addition to the luminaire - LINEAR XL POWER CLASS BASIC (2 STRIPS) - LINEAR XL POWER CLASS MEDIUM (3 STRIPS) - LINEAR XL POWER CLASS FORTE (4 STRIPS)

Light output 1 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	5.75 W	CRI	-29
Total flux	80 lm	LOR	100%
Luminous efficacy	14 lm/W	Total power	5.75 W

Light output 2 (integrated)




Lamp type	LED	CCT	7247 K
Nominal lamp power	5.75 W	CRI	-18
Total flux	230 lm	LOR	100%
Luminous efficacy	40 lm/W	Total power	5.75 W

Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	5.75 W	CRI	-50
Total flux	50 lm	LOR	100%
Luminous efficacy	9 lm/W	Total power	5.75 W

Light output 4 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	5.75 W	CRI	80
Total flux	240 lm	LOR	100%
Luminous efficacy	42 lm/W	Total power	5.75 W

Mounting mode

Pendant

Shape and measurements

Length: 46.22 in

Width: 2.99 in

Height: 0.59 in

Weight: 0.4 kg

Adjustability

Fixed

Electric

System power: 23 W

Color adjustable

Appliance Class: I

Protection

IP: 20

Other operating numbers

Ambient temperature range: 14...113°F