Product data sheet


FLEX50
FX50H-568402-LXXXM
EGLO



IP 20


pendant mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	532 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	3.98 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	532 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	3.98 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	532 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	3.98 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	532 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	3.98 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	532 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	3.98 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	532 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	3.98 W

Mounting mode

Pendant

Shape and measurements

Length: 53.46 in

Width: 61.22 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 23.88 W

Protection

IP: 20

Designation labels: CE