

Product data sheet

MIC 6 BRACKET MOUNTED FLOODLIGHTS


MI-50431-M-W40

LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 135,000, > 50,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing with a chemical chromatised protection before powder coating, ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	38.3 W	CRI	80
Total flux	4152 lm	LOR	100%
Luminous efficacy	108 lm/W	Total power	38.3 W

Mounting mode

Wall mounted

Shape and measurements

Height: 27.95 in

Diameter: 10.24 in

Weight: 5.8 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 38.3 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 07

Surface temperature: 40°C